

AC 6C Ellipse Frame



SIZE :

172x150x51mm (6.69"x5.91"x2.01")

CONSTRUCTION :

- Die-cast aluminum housing
- Glass fiber reinforced plastic:
Impeller are UL 94V-0 rating
- Capacitor-start motor/Shaded pole motor
- Thermat Protected/Impedance protected
- Leader wire available

OPERATING TEMPERATURE :

Ball bearing - 30°C to +75°C

WEIGHT :

945 grams

Specifications

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	FREQUENCY	MAX. RATED CURRENT	MAX. INPUT POWER	SPEED R.P.M.	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE dB-A
		VAC	Hz	mA	W		m ³ /min	CFM	mmH ₂ O	IN H ₂ O	
6C-115HBC	Ball	115	50/60	580/550	45/43	2850/3400	5.1/6.0	181/210	13.9/16.5	0.6/0.7	55.5/60.3
6C-115HBS	Ball	115	50/60	640/540	48/46	2750/3100	5.0/6.0	176/211.7	13/15.3	0.5/0.6	54.5/57.5
6C-230HBC	Ball	230	50/60	140/160	30/30	2850/3400	5.1/6.0	181/210	13.9/16.5	0.6/0.7	55.5/60.3
6C-230HBS	Ball	230	50/60	300/280	46/44	2750/3100	5.0/6.0	176/211.7	13/15.3	0.5/0.6	54.5/57.5
6C-380HBS	Ball	380	50/60	300/280	46/44	2750/3100	5.0/6.0	176/211.7	13/15.3	0.5/0.6	54.5/57.5

