



**SIZE :**

92x92x25mm (3.62"x3.62"x0.98")

**CONSTRUCTION :**

- Die-cast aluminum housing
- Glass fiber reinforced plastic:  
Impeller are UL 94V-0 rating
- Impedance protected
- Leader wire or Terminal is available

**OPERATING TEMPERATURE :**

Ball bearing - 30°C to +75°C  
Sleeve bearing - 10°C to +70°C

**WEIGHT :**

280 grams

**Specifications**

Specifications are subject to change without notice

MODEL NO.	BEARING	RATED VOLTAGE	FREQUENCY	MAX. RATED CURRENT	MAX. INPUT POWER	SPEED	MAX. AIR FLOW		MAX. AIR PRESSURE		NOISE
		VAC	Hz	mA	W	R.P.M.	m <sup>3</sup> /min	CFM	mmH <sub>2</sub> O	IN H <sub>2</sub> O	
9P-115LB	Ball	115	50/60	140/120	14/13	1800/2300	0.6/0.7	20.0/25.4	1.9/3.1	0.1/0.2	28/35
9P-115LS	Sleeve										
9P-115HB	Ball	115	50/60	160/140	16/14	2400/2900	0.8/1.0	26.6/31.9	3.2/4.5	0.1/0.2	35/41
9P-115HS	Sleeve										
9P-230LB	Ball	230	50/60	80/70	16/14	1800/2300	0.6/0.7	20.0/25.4	1.9/3.1	0.1/0.2	28/35
9P-230LS	Sleeve										
9P-230HB	Ball	230	50/60	80/70	16/14	2400/2900	0.8/0.9	26.6/31.9	3.2/4.5	0.1/0.2	35/41
9P-230HS	Sleeve										

